

Silicon NPN transistor epitaxial type

D5939

[Applications]

Inverter, Strobo Flash, DC-DC converter
with high current and small collector-emitter saturation voltage.
High power switching with high collector current.

[Feature]

Small collector-emitter saturation voltage VCE(sat)= 0.28V(Typ.) at IC= 3A, IB= 100mA
High collector current IC= 5A
High emitter-base breakdown voltage BVEBO= 9V

[Absolute maximum ratings (Ta=25C)]

Characteristic	Symbol	Maximum ratings	Unit
Collector-base voltage	VCBO	50	V
Collector-emitter voltage	VCEO	20	V
Emitter-base voltage	VEBO	9	V
Collector current	IC	5	A
Junction temperature	Tj	150	C
Storage temperature	Tstg	-55 to 150	C

[Electrical characteristics (Ta=25C)]

Characteristic	Symbol	Min.	Typ.	Max.	Unit	Conditions
Collector-base breakdown voltage	BVCBO	50	-	-	V	IC= 10uA, IE= 0A
Collector-emitter breakdown voltage	BVCEO	20	-	-	V	IC= 1mA, IB= 0A
Emitter-base breakdown voltage	BVEBO	9	-	-	V	IE= 10uA, IC= 0A
Collector cut-off current	ICBO	-	-	100	nA	VCB= 40V, IE= 0A
Collector cut-off current	ICEO	-	-	1	uA	VCE= 10V, IB= 0A
Emitter cut-off current	IEBO	-	-	100	nA	VEB= 7V, IE= 0A
DC current gain 1	hFE 1	230	-	600	-	VCE= 2V, IC= 500mA
DC current gain 2	hFE 2	150	-	-	-	VCE= 2V, IC= 2A
Collector-emitter saturation voltage	VCE(sat)	-	0.28	0.8	V	IC= 3A, IB= 100mA
Transition frequency	f T	-	150	-	MHz	VCE= 6V, IE= -50mA
Collector output capacitance	Cob	-	-	50	pF	VCB= 10V, f = 1MHz, IE= 0A

Notice 1) These are measured data of transistors assembled by PHENITEC SEMICONDUCTOR Corp. and are for reference only.

Notice 2) The contents described herein are subject to change without notice.

No. D5939-20051220

Fig.1 hFE - IC
at VCE= 2V, Ta= 25C




Fig.2 VCE(sat) - IC
at IC/IB= 30, Ta= 25C




Fig.3 VBE(sat) - IC
at IC/IB=30, Ta= 25C




Fig.4 fT - IE
at VCE= 6V, Ta= 25C




Fig.5 Cob - VCB
at f= 1MHz, Ta= 25C

