

Silicon NPN transistor epitaxial type
6C082
[Applications]

Low VCE(sat)

[Feature]

Low collector saturation voltage VCE(sat)= 0.3V(Max.) at IC= 50mA, IB= 5mA

[Absolute maximum ratings (Ta=25C)]

Characteristic	Symbol	Maximum ratings	Unit
Collector-base voltage	VCBO	60	V
Collector-emitter voltage	VCEO	40	V
Emitter-base voltage	VEBO	6	V
Collector current	IC	0.2	A
Junction temperature	Tj	150	C
Storage temperature	Tstg	-55 to 150	C

[Electrical characteristics (Ta=25C)]

Characteristic	Symbol	Min.	Typ.	Max.	Unit	Conditions
Collector-base breakdown voltage	BVCBO	60	-	-	V	IC= 10uA, IE= 0A
Collector-emitter breakdown voltage	BVCEO	40	-	-	V	IC= 10mA, IB= 0A
Emitter-base breakdown voltage	BVEBO	6	-	-	V	IE= 10uA, IC= 0A
DC current gain 1	hFE 1	40	-	-	-	VCE= 1V, IC= 0.1mA
DC current gain 2	hFE 2	70	-	-	-	VCE= 1V, IC= 1mA
DC current gain 3	hFE 3	90	-	333	-	VCE= 1V, IC= 10mA
DC current gain 4	hFE 4	60	-	-	-	VCE= 1V, IC= 50mA
DC current gain 5	hFE 5	30	-	-	-	VCE= 1V, IC= 100mA
Collector-emitter saturation voltage 1	VCE(sat) 1	-	-	0.2	V	IC= 10mA, IB= 1mA
Collector-emitter saturation voltage 2	VCE(sat) 2	-	-	0.3	V	IC= 50mA, IB= 5mA
Base-emitter saturation voltage	VBE(sat)	-	-	0.95	V	IC= 50mA, IB= 5mA
Transition frequency	fT	250	-	-	MHz	VCE= 20V, IE= -10mA
Collector output capacitance	Cob	-	-	4	pF	VCB= 5V, f= 1MHz, IE= 0A

Notice 1) These are measured data of transistors assembled by PHENITEC SEMICONDUCTOR Corp. and are for reference only.

Notice 2) The contents described herein are subject to change without notice.

No. 6C082-20190906